

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1070	Southwest Head Radiobeacon (C)						<i>Remove from list.</i>
							* 22/00
16030	<i>Buzzards Bay Lighted Gong Buoy 5</i>	41 29 00 N 70 57 24 W	FI G 6s		4	Green.	Removed when endangered by ice.
	*	*	*			*	* 22/00
16035	<i>Buzzards Bay Lighted Bell Buoy 6</i> Off southeast side of ledge.	41 27 54 N 70 56 36 W	FI R 4s		4	Red.	
	*	*	*			*	* 22/00
18925	Borden Flats Light	41 42 18 N 71 10 30 W	FI W 2.5s	47	11	White conical tower, on brown cylindrical pier.	HORN: 1 blast ev 10s (1s bl).
							* 22/00
HEMPSTEAD HARBOR TO TALLMAN ISLAND (Chart 12366)							
East River Main Channel							
27215	Whitestone Point Light 1	40 48 06 N 73 49 12 W	F G	56	10	SG on black skeleton tower.	BELL: 1 stroke ev 15s. Remotely controlled.
				*			22/00
36165	- LIGHT 20		FI R 4s	30	6	TR on skeleton tower.	
				*			22/00
36245	- LIGHT 42		FI R 4s	30	4	TR on square skeleton tower.	
				*			22/00
36315	- LIGHT 58		FI R 4s	30	5	TR on skeleton tower with red base.	
				*			22/00
36750	- LIGHT 14		FI R 4s	33	5	TR on skeleton tower.	
				*			22/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2635	- <i>Wreck Lighted Buoy WR10R</i> 93 yds, 273° from wreck. Marks SS PHEONIX.	39 32 12 N 75 32 30 W	Q R		3	Red	Buoy replaced by a lighted ice buoy of lower intensity from Jan. 1 to Feb. 28.
	*	*		*	*	*	* 22/00
*7493	<i>UMCES Lighted Buoy</i>		FI Y 6s			Yellow.	Private aid.
							22/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
20935	- Channel Lighted Buoy 13		Q G		4	Green.	
			*				22/00
30330	BALD HEAD SHOAL CHANNEL RANGE FRONT LIGHT	33 53 00 N 77 59 48 W	Iso W 2s(Day) Iso W 2s(Night)	18 15		Skeleton tower on platform.	Lighted throughout 24 hours. DAY: Visible on rangeline only. NIGHT: Visible all around; higher intensity on rangeline.
		*		*			22/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*907	McMoran-113-18 Lighted Buoy Marks subsea installation.	28 58 24 N 92 28 54 W	Q R			Red.	SIGN: MOXY-VR-144-3. Private aid.
							22/00
13234	Magnolia Anchorage Upper Daybeacon 47.6	29 33 42 N 89 47 12 W				NY on pile.	Ra ref.
	*	*					22/00
13397	Alliance Anchorage Lower Daybeacon 63.8	29 42 00 N 89 59 00 W				NY on pile.	Ra ref.
		*					22/00
13408	Wills Point Anchorage Upper Daybeacon 67.6	29 45 06 N 90 01 00 W				NY on pile.	Ra ref.
		*					22/00
13483	Lower 12 Mile Point Anchorage Upper Daybeacon 80.8	29 52 06 N 89 55 24 W				NY on pile.	Ra ref.
		*					22/00
NEW ORLEANS HARBOR (Chart 11368)							
Head of Passes to New Orleans							
<i>Designations left descending bank (LDB) and right descending bank (RDB) are as seen from a vessel going downstream. Mileage given indicates the number of miles above Head of Passes Junction Light.</i>							
13579 33257	New Orleans General Anchorage Lower Daybeacon 90.1	29 55 54 N 89 59 42 W				NY on pile.	Ra ref.
	*	*					22/00
15020	- LIGHT 22	29 09 06 N 89 23 54 W	F I R 4s	15	3	TR on pile.	
		*					22/00
22690	- Entrance Channel Lighted Buoy 9 100 feet outside channel limit.	29 20 36 N 94 42 30 W	Q G		4	Green.	
		*					22/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
28350 40740	- RANGE C FRONT LIGHT	26 02 15 N 97 12 42 W	Q G Q G	25 27	3	KRW-I on skeleton tower on piles.	For downbound traffic. Passing light visible all around.
			*	*			* 22/00
28395 40785	- RANGE B FRONT LIGHT	26 00 48 N 97 15 42 W	Q R Q R	25 27	3	KRW-I on skeleton tower on piles.	For upbound traffic. Passing light visible all around.
			*	*			* 22/00
28435 40815	- RANGE G FRONT LIGHT	25 58 48 N 97 19 00 W	Q G Q G	25 27	3	KRW-I on skeleton tower on piles.	For downbound traffic. Passing light visible all around.
			*	*			* 22/00
33080	- Buoy 24	30 08 48 N 89 37 12 W				Red nun with yellow triangle.	
		*					22/00
33257 13597	New Orleans General Anchorage Lower Daybeacon 90.1	29 55 54 N 89 59 42 W				NY on pile.	Ra ref.
	*	*					22/00
40135	- LIGHT 4	26 21 18 N 97 19 24 W	Q R	17	3	TR-TY on pile.	
		*				*	22/00
40740 28350	- RANGE C FRONT LIGHT	26 02 15 N 97 12 42 W	Q G Q G	25 27	3	KRW-I on skeleton tower on piles.	For downbound traffic. Passing light visible all around.
			*	*	*		* 22/00
40785 28395	- RANGE B FRONT LIGHT	26 00 48 N 97 15 42 W	Q R Q R	25 27	3	KRW-I on skeleton tower on piles.	For upbound traffic. Passing light visible all around.
			*	*		*	* 22/00
40815 28435	- RANGE G FRONT LIGHT	25 58 48 N 97 19 00 W	Q G Q G	25 27	3	KRW-I on skeleton tower.	For downbound traffic. Passing light visible all around.
			*	*			* 22/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2890	- BREAKWATER LIGHT EAST	33 45 30 N 118 10 54 W	Q Y			On post. 4	Private aid. HORN: 1 blast ev 20s (2s bl).
			*				22/00
17435	- RANGE REAR LIGHT 325 yards, 144.6° from front light.		Iso G 6s	40		KRB on skeleton tower.	Visible all around, higher intensity on rangeline.
							* 22/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 1999

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
17485	OLYMPIA INNER RANGE REAR LIGHT 235 yards, 354° from front light.		Iso W 6s	23		KRB on dolphin.	Visible all around, higher intensity on rangeline. * 22/00
20420	WALKER ROCK LIGHT (C)	48 55 24 N 123 29 36 W	FI (3) W 12s 0.5s fl 2s ec. 0.5s fl 2s ec. 0.5s fl 6.5s ec. (G, W & R Sectors)	24	6	White circular tower.	Ra ref. Green sector 082° to 088°, white sector 088° to 092°, red sector 092° to 099°. * 22/00
20525	THRASHER ROCK LIGHT (C)	49 09 00 N 123 38 24 W	FI (3) W 12s 0.5s fl 2s ec. 0.5s fl 2s ec. 0.5s fl 6.5s ec.	36		White circular tower with green band at top.	RACON: X (—••—). Ra Ref. * 22/00
29380	- ENTRANCE RANGE FRONT LIGHT	21 19 36 N 157 58 18 W	Q R F R	51 48		KRW on skeleton tower.	Quick flashing red light visible 4° on either side of centerline over fixed line of red light on daymark. * 22/00
29400	- LIGHT 5	21 18 54 N 157 58 00 W	FI G 2.5s	15	4	SG on pile.	* 22/00
29430	- WEST LOCH JUNCTION LIGHT W	21 20 30 N 157 58 18 W	FI (2+1) G 6s	15	5	JG on pile.	* 22/00
Pearl Harbor West Loch							
29510	- ENTRANCE RANGE FRONT LIGHT	21 21 06 N 157 59 00 W	F G	32		KRW on skeleton tower.	Visible 4° each side of rangeline. * 22/00
29520	- Daybeacon 1	21 20 24 N 157 58 30 W				SG on pile.	* 22/00

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5085	SQUAW ISLAND LIGHT 12		FI R 4s	25 8	6	TR on white skeleton tower.	* 20/00
*5849.3	LEMARIN ENTRANCE NORHT LIGHT	41 33 36 N 82 51 12 W	F G	20 6		On concrete pile.	Maintained from Apr. 15 to Nov. 15. Private aid. 17/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*5849.4	LEMARIN ENTRANCE SOUTH LIGHT	41 33 30 N 82 51 12 W	F R	20 6		On concrete pile.	Maintained from Apr. 15 to Nov. 15. Private aid.
							17/00
	*Change Note to Read:						
	Pier 75 Detached Breakwater						
	<i>*Lights maintained from Apr. 1 to Dec. 1.</i>						
6370	- LIGHT A	41 37 36 N 83 32 42 W	Q W	3 1		On southeast corner of detached breakwater.	Private aid.
	*			*		*	21/00
6375	- LIGHT B		Q W	3 1		On detached breakwater.	Private aid.
	*			*		*	21/00
6380	- LIGHT C		Q W	3 1		On detached breakwater.	Private aid.
	*			*		*	21/00
6385	- LIGHT D		Q W	3 1		On southwest corner of detached breakwater.	Private aid.
	*			*		*	21/00
6390	- LIGHT E		Q W	3 1		On northeast corner of detached breakwater.	Private aid.
	*			*		*	21/00
6395	- LIGHT F		Q W	3 1		On detached breakwater.	Private aid.
	*			*		*	21/00
6400	- LIGHT G		Q W	3 1		On detached breakwater.	Private aid.
	*			*		*	21/00
6405	- LIGHT H		Q W	3 1		On northwest corner of detached breakwater.	Private aid.
	*			*		*	21/00
7180	- Lighted Buoy 73D (C)						Remove from list.
							*
							21/00
13345	- Lighted Buoy 59		FI G 2.5s		4	Green.	Replaced by LIB from Dec. 7 to Apr. 21.
			*				19/00
13353	- LIGHT 61	46 20 00 N 84 11 00 W	Q G	26 8	4	SG on post.	
			*				21/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
13380	- Lighted Buoy 63		FI G 2.5s		4	Green.	Replaced by can from Dec. 7 to Apr. 21.
			*				17/00
13395	- Lighted Buoy 66		FI R 4s		4	Red.	Replaced by nun from Dec. 7 to Apr. 21.
			*				17/00
13400	- Lighted Buoy 67		FI G 4s		4	Green.	Replaced by can from Dec. 7 to Apr. 21.
			*				17/00
14010	FRECHETTE POINT LIGHT 91						Remove from list.
							* 17/00
14505	- Shoal Buoy 41 Marks north side of shoal.						Remove from list.
							* 20/00
DULUTH - SUPERIOR HARBOR (Chart 14975)							
Superior Entry							
15595	- South Breakwater Light	46 42 36 N 92 00 24 W	FI G 5s	70 21	13	White cylindrical tower on fog signal building.	HORN: 1 blast ev 30s (3s bl). Operates from May 1 to Oct. 20.
					*		19/00
15600	- NORTH BREAKWATER LIGHT	46 42 42 N 92 00 30 W	Q R	38 12	4	TR on post.	
					*		19/00
15610	- INNER SOUTH PIERHEAD LIGHT	46 42 30 N 92 00 48 W	Iso G 6s	35 11	4	SG on post.	
					*		19/00
15845	- South Breakwater Outer Light	46 46 48 N 92 05 18 W	F G	44 13	17 35	White tower on fog signal building.	HORN (2300-0700): 1 blast ev 60s for 2 min (4s bl-52s si), followed by 2 blasts (2s bl-1s si-5s bl-56s si).
					*		* 19/00
15855	- North Pier Light	46 46 54 N 92 05 18 W	Iso R 6s	43 13	11 37	White cylindrical tower with black top and base.	
					*		19/00
15860	- South Breakwater Inner Light	46 46 44 N 92 05 31 W	FI W 5s	68 21	18 67	Black cylindrical tower with white lantern room.	Light obscured from 270° through 325°.
					*		19/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
17925	- South Pierhead Light	45 19 00 N 85 15 54 W	FI R 4s	41 12	10	On white square tower.	HORN: 1 blast ev 30s (3s bl). Operates from May 1 to Oct. 20.
			*		*		20/00
18400	S.S. CITY OF MILWAUKEE LIGHT						Remove from list.
							* 21/00
18710	- South Pierhead Light	43 13 36 N 86 20 29 W	FI R 4s	50 15	10	Conical tower. 48	
					*		17/00
CHICAGO HARBOR (Chart 14928)							
19930	THIRTY-FIRST STREET OUTER JETTY LIGHT	41 50 24 N 87 36 18 W	FI Y 2.5s	29 9		NW on cylindrical tower.	Maintained from Apr. 15 to Dec. 1. Private aid.
	*		*	*		*	22/00
*19934	THIRTY-FIRST STREET INNER JETTY LIGHT	41 50 24 N 87 36 24 W	FI Y 2.5s	26 8		NW on cylindrical tower.	Maintained from Apr. 15 to Dec. 1. Private aid.
							22/00
Zion Intake							
<i>Lights maintained from Apr. 1 to Oct. 31.</i>							
20355	- Lighted Buoy A	42 26 36 N 87 47 24 W	FI W 2.5s			White can with orange bands and diamond.	Private aid.
		*					* 18/00
20360	- WEST LIGHT	42 26 36 N 87 47 30 W	Q W	5 2		NW on post.	Private aid.
			*	*		*	18/00
20365	- SOUTH LIGHT						Remove from list.
							* 18/00
20370	- EAST LIGHT						Remove from list.
							* 18/00
20375	- NORTH LIGHT						Remove from list.
							* 18/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.